

Nuxeo Issue Tracker

JQL Query: project in (NXP, NXCM) AND resolution = Fixed AND fixVersion = "5.6" AND ("Impact type" = "API change" OR "Upgrade notes" is not EMPTY) ORDER BY component ASC
Displaying issues 1 to 80 of 80 matching issues. as at: 11/09/12

PKey	Summary	Upgrade notes	Components	Fix Version/s	Status	Created
↓ NXP-9348	Allow removing of activities list instead of activity ids list	<pre> {{ActivityStreamService#removeActivities(Collection<Serializable activityIds>)} changed to {{ActivityStreamService#removeActivities(Collection<Activity> activities)}} </pre> <p>See <code>{{MiniMessageServiceImpl#removeMiniMessage}}</code> or <code>{{RatingServiceImpl#cancelRate}}</code> to see how to migrate code.</p>	Activity	5.6-RC1, 5.6	Resolved	21/05/12
↓ NXP-8920	Add missing API to fetch the history of a document	The default definition of the DOCUMENT_HISTORY_PROVIDER provider has been replaced, but the old one is still accessible under name DOCUMENT_HISTORY_PROVIDER_OLD. The default contentview has been updated accordingly.	Audit	5.6-RC1, 5.6	Resolved	27/02/12
↓ NXP-9322	mail transport config not taken in account in SendMail automation operation	<p>In tomcat environment, for hot-fixed instance, if protocol switch needed, apply the attached templates using the following command in the nuxeo runtime</p> <pre>patch -p0 << /tmp/templates.patch</pre> <p>Here is the configuration changes applied :</p> <ul style="list-style-type: none"> - the mail session is bound into the JNDI using the nuxeo's resource factory <code>{{org.nuxeo.ecm.platform.ec.notification.email.EmailResourceFactory}}</code>. - The 'mail.smtp.' and 'mail.pop3.' properties have been renamed respectively into 'mail.transport.' and 'mail.store.'. - user credentials may be filled for both protocols using the keys 'mail.user' and 'mail.password' or by protocols using the keys 'mail.(protocol).user' and 'mail.(protocol).password' and properties are enabled by protocol using the keys <code>{{user}}</code> and <code>{{password}}</code>. <p>For jboss environment, you should edit by hand the mail service configuration in jboss templates and apply the same parameters changes</p>	Automation	5.4.2-HF23, 5.5.0-HF08, 5.6-RC1, 5.6	Resolved	10/05/12
↑ NXP-9662	iterable results not closed in automation		Automation, Core SQL Storage	5.5.0-HF14, 5.6	Resolved	11/07/12
↓ NXP-9270	During mailbox synchronization , deleting the mailboxes for users and groups that no longer exists in LDAP/SQL directory should be configurable	The property "cm.syncro.delete.mailboxes" is now used to control if the old mailboxes are deleted or not during synchronization. By default, if this property is not specified, the mailboxes are not deleted. (contrary to previous versions)	CMF	5.5.0-HF07, 5.6-RC1, 5.6	Resolved	24/04/12
↓ NXP-9287	Expose ecm:name to CMIS as nuxeo:pathSegment	New CMIS-level property: nuxeo:pathSegment. Also usable in CMISQL. It is mapped to Nuxeo's DocumentModel.getName(), which is the ecm:name in NXQL.	CMIS	5.5.0-HF07, 5.6-RC1, 5.6	Resolved	02/05/12
↓ NXP-9550	Switch to OpenCMIS 0.7.0	Upgrade to OpenCMIS 0.6.0.	CMIS	5.6-RC1, 5.6	Resolved	20/06/12
↓ NXP-9251	Add Freemarker functionality to the Nuxeo configuration templates	<p>Due to some constraints of the Freemarker data model (see description), a few configuration keys need to be changed:</p> <ul style="list-style-type: none"> - nuxeo.templates.parsing.extensions -> nuxeo.plaintext_parsing_extensions - nuxeo.db.user.separator.key -> nuxeo.db.user_separator_key - nuxeo.server.tomcat-admin.port -> nuxeo.server.tomcat_admin.port <p>and some java properties will not be available in Freemarker:</p> <ul style="list-style-type: none"> - java.vendor.url - java.vendor.url.bug 	Configuration	5.6-RC1, 5.6	Resolved	18/04/12
↓ NXP-9103	Marketplace packages shouldn't modify distribution.properties	<p>Since packages of the DM & DAM family are now just an addon on the platform, they shouldn't touch distribution.properties, which describes the underlying platform.</p> <p>Stage 1: remove those actions from our packages Stage 2: modify the tasks so that anything that isn't a hotfix is prevented from modifying distribution.properties (check status of NXP-9086 with MG/JC first)</p>	Connect	5.6-RC1, 5.6	Resolved	25/03/12
↓ NXP-9432	Add support for multiple Connect channels to nuxeo-connect-client	<p>nuxeo-connect-client: new methods org.nuxeo.connect.packages.PackageSource.getId()</p> <p>nuxeo-core-api: New constructor org.nuxeo.ecm.core.api.PathRef(PathRef, String) getVisibility() added on multiple classes</p>	Connect	5.6-RC1, 5.6	Resolved	05/06/12
↓ NXP-8918	Allow PDF/A file conversion	<p>When calling a converter, you can now pass an additional parameter to state that PDF/A-1 conformance is needed:</p> <pre>parameters.put("PDF/A-1", Boolean.TRUE); conversionService.convert("any2pdf", blobHolder, parameters);</pre>	Convert	5.6-RC1, 5.6	Resolved	24/02/12
↓ NXP-8240	Add public detach/attach methods on DocumentModel	<p>New APIs:</p> <ul style="list-style-type: none"> - DocumentModel.detach() - DocumentModel.attach() 	Core	5.6-RC1, 5.6	Resolved	27/12/11
↑ NXP-8933	When adding a comment, fired event loses the comment property	The Comment document is now stored in the property "comment_document"	Comments, Core	5.5.0-HF05, 5.6-RC1, 5.6	Resolved	28/02/12
↓ NXP-8945	Use SystemPrincipal when creating system Principal in LocalSession	The org.nuxeo.ecm.platform.login.SystemPrincipal class has moved to nuxeo-core-api: org.nuxeo.ecm.core.api.SystemPrincipal	Core	5.5.0-HF04, 5.6-RC1, 5.6	Resolved	28/02/12
↓ NXP-9193	Add event filtering to async listeners that are too general	<p>PostCommitFilteringEventListener is a new sub-interface of PostCommitEventListener that can be used.</p> <p>It defines a method acceptEvent that can be used to decide at event time (synchronously) whether this listener is worth calling with this event.</p>	Core	5.6-RC1, 5.6	Resolved	10/04/12
↓ NXP-9241	Move SchedulerService to nuxeo-core-event	<p>The internal APIs related to the SchedulerService have been moved to package org.nuxeo.ecm.core.scheduler.</p> <p>Bundle nuxeo-platform-scheduler-core (org.nuxeo.ecm.platform.scheduler.core) has been removed.</p>	Core	5.6-RC1, 5.6	Resolved	18/04/12

PKey	Summary	Upgrade notes	Components	Fix Version/s	Status	Created
		Note that the component name "org.nuxeo.ecm.platform.scheduler.core.service.SchedulerRegistryService" used in extension points is still available transparently through an alias for compatibility. For those able to migrate, the new one is "org.nuxeo.ecm.core.scheduler.SchedulerService".				
↓ NXP-9373	Add a document XML exporter service	Added the DocumentXMLExporter interface that provides the exportXML, exportXMLAsInputSource and exportXMLAsByteArray methods.	Core	5.6-RC1, 5.6	Resolved	25/05/12
⊙ NXP-9763	Mixup of sessions when several from multiple repositories are used at the same time	For Tomcat, the pool configuration which used to be done through a <Resource> section in nuxeo.xml is now done through a <pool> section in the repository configuration file (default-repository-config.xml). The nuxeo.conf properties "nuxeo.vcs.min-pool-size" and "nuxeo.vcs.max-pool-size" are still used in the same way as before. If further config (like blockingTimeoutMillis or idleTimeoutMinutes) is needed then the new template to copy and modify is default-repository-config.xml.nxftl.	Core	5.6-RC3, 5.6	Resolved	24/07/12
↑ NXP-8221	Documents created in old versions of Nuxeo DM cannot be found when doing a fulltext search on the title field only	On PostgreSQL the following SQL query updates the "fulltext_title" from the current value of the "dublincore:title" field and fixes the issue. UPDATE fulltext SET simpletext_title = NX_TO_TSVECTOR("dublincore"."title") FROM dublincore WHERE "fulltext"."id" = "dublincore"."id";	Core SQL Storage	5.6-RC1, 5.6	Resolved	22/12/11
↓ NXP-8797	Make fulltext normalization algorithm configurable	To customizing splitting/parsing, a repository config can now specify a custom fulltext parser class using: <fulltext analyzer="..." parser="some.parser.class" ...> where some.parser.class must be a subclass of org.nuxeo.ecm.core.storage.sql.FulltextParser. It's likely that implementors will want to override method parse().	Core SQL Storage	5.4.2-HF17, 5.5.0-HF11, 5.6-RC1, 5.6	Resolved	06/02/12
↓ NXP-8937	Allow Dialect subclassing	To use a specific dialect, set the system property "nuxeo.vcs.dialect" to the class name of the Dialect subclass to use. To override only the dialect for a given database, for example PostgreSQL, use the system property "nuxeo.vcs.dialect.PostgreSQL".	Core SQL Storage	5.4.2-HF18, 5.5.0-HF04, 5.6-RC1, 5.6	Resolved	28/02/12
↓ NXP-9541	Improve Oracle + Nuxeo cluster node removal behavior	The format of the tables CLUSTER_NODES and CLUSTER_INVALS has changed and they ***MUST*** be dropped while the server is stopped. DROP TABLE "CLUSTER_NODES"; DROP TABLE "CLUSTER_INVALS"; If you don't want to let Nuxeo recreate them (when using noDDL), the new DDL to execute by hand is: CREATE TABLE "CLUSTER_NODES" ("NODEID" VARCHAR(25), "CREATED" TIMESTAMP); CREATE TABLE "CLUSTER_INVALS" ("NODEID" VARCHAR(25), "ID" VARCHAR(36), "FRAGMENTS" VARCHAR(4000), "KIND" NUMBER(3,0)); CREATE INDEX "CLUSTER_INVALS_NODEID_IDX" ON "CLUSTER_INVALS" ("NODEID");	Core SQL Storage	5.4.2-HF25, 5.5.0-HF10, 5.6-RC1,5.6	Resolved	19/06/12
↓ NXP-9817	Remove size limit on read acl for Oracle	If you are subject to this bug (ORA-06502), you need to drop the ACLR table before starting Nuxeo. The ACLR table will be populated at startup, if you have lots of documents it can take time and you may need to either increase the startup delay (launcher.start.max.wait in the nuxeo.conf) either run the following SQL command DROP TABLE ACLR; BEGIN nx_rebuild_read_acls; END;	Core SQL Storage	5.5.0-HF12, 5.5.0-HF13, 5.6-RC3, 5.6	Resolved	01/08/12
↑ NXP-9395	Provide a property to remove default sort in DAM	new property {{org.nuxeo.dam.add.default.sort}}	DAM	5.5.0-HF08, 5.6-RC1, 5.6	Resolved	30/05/12
↓ NXP-8998	Allow digital PDF signature of any file	The SignatureService API has been reworked completely. The SignActions Seam component has a new API as well. Its default behavior can be customized using system properties: - org.nuxeo.ecm.signature.pdfa=true/false: whether to produce PDF/A files (default is false) - org.nuxeo.ecm.signature.disposition.pdf=replace/archive/attach: what to do with signed files produced from PDFs (default is archive) - org.nuxeo.ecm.signature.disposition.notpdf=replace/archive/attach: what to do with signed files produced from non-PDFs (default is attach) - org.nuxeo.ecm.signature.archive.filename.format: the SimpleDateFormat of the suffix to append to the filename when archiving (default is "(archive' yyyy-MM-dd HH:mm:ss)") The dispositions (SigningDisposition enum) are: - replace: replace the main blob with the signed one - archive: replace the main blob with the signed one and archive the original - attach: put the signed blob as an attachment	Digital Signature	5.6-RC1, 5.6	Resolved	06/03/12
↓ NXP-9132	Add a parameter in digest login plugin to specify the field use to retrieve password	The new parameter "passwordField" can be set to specify the field used to get the digest: <extension target="org.nuxeo.ecm.platform.login.LoginPluginRegistry" point="plugin"> <LoginPlugin name="DigestLoginPlugin" class="org.nuxeo.ecm.ui.web.auth.digest.DigestLoginPlugin"> <enabled>true</enabled> <parameters name="passwordField">password</parameters> </LoginPlugin> </extension>	Directory	5.5.0-HF06, 5.6-RC1, 5.6	Resolved	30/03/12
↓ NXP-9400	Fix update entry in multidirectory	don't silently ignore attempts to update nonexisting entries in MemoryDirectory	Directory	5.4.2-HF23, 5.5.0-HF08, 5.6-RC1, 5.6	Resolved	31/05/12

PKey	Summary	Upgrade notes	Components	Fix Version/s	Status	Created
↓ NXP-9745	Improve Platform Explorer	Not sure that improve "Contribution display : list fragment by fragment is done"	Explorer	5.6	Resolved	19/07/12
↑ NXP-9086	Refactor Nuxeo connect for standalone capability	API changes on org.nuxeo.connect.update.* Removed Maven artifacts: org.nuxeo.ecm.platform:nuxeo-connect-offline-update New Maven artifacts: org.nuxeo.runtime:nuxeo-connect-standalone	Admin Center ,Installers / Admin tools ,Launcher ,Connect	5.6-RC1, 5.6	Resolved	21/03/12
↑ NXP-9210	Make the clone.py script fallback on master	New "-f" option in clone.py which allows to fallback on a given branch when the wanted one is not found.	Installers / Admin tools	5.6-RC1, 5.6	Resolved	12/04/12
↓ NXP-4801	NXP-4800 Display a standalone widget in a given mode	nxl:widget tag now accepts alternatives to the widget instance, like the widget name or a widget definition	Layouts / Widgets	5.6-RC1, 5.6	Resolved	25/02/10
↓ NXP-4933	NXP-4800 Provide more widget presentation options	widget template list_subwidget_template.xhtml is now deprecated, and tag nxl:widgetType accepts subwidgets.	Layouts / Widgets	5.6	Resolved	23/03/10
↓ NXP-4937	NXP-4800 Add a "decorative" or "container" widget type	Added marker "handlingLabels" on widget definition: when set to true, the default layout template will not display the widget label and help label and will let the widget render it (taking both the label and widget place in the rendering)	Layouts / Widgets	5.6-RC1, 5.6	Resolved	23/03/10
↓ NXP-9234	Allow referencing of a widget subwidgets	The json export has changed to include category in widget references: for instance now we have {"widgets": [{"name": "nature"}]}, instead of {"widgets": [{"nature"}]}. Now possible to reference subwidgets (defined locally or globally) using the same syntax than when referencing widgets in rows, for instance: <widget name="testWidgetWithSubWidgetRefs" type="test"> <subWidgetRefs> <widget>globalSubWidget</widget> <widget>testLocalSubWidget</widget> </subWidgetRefs> </widget>	Layouts / Widgets	5.6-RC1, 5.6	Resolved	16/04/12
↓ NXP-9286	Allow empty field mapping in layout widgets	widget template complex_list_item_widget_template.xhtml is now useless, and variable #{fieldOrValue} is now available for default binding in widget templates.	Layouts / Widgets	5.6-RC1, 5.6	Resolved	02/05/12
↓ NXP-9357	Add back a date formatter guessing the century	Widgets specifying using the "short" format should now use "shortWithCentury" instead. Default formatters now use the "shortWithCentury" format so behaviour does not change for them.	Layouts / Widgets	5.6-RC1, 5.6	Resolved	22/05/12
↓ NXP-9892	Add API to check if a layout definition is empty	added LayoutDefinition#isEmpty	Layouts / Widgets	5.6	Resolved	17/08/12
↓ NXP-9451	Add an extension point to filter when notifications are sent	New extension point notificationListenerVeto	Notifications	5.6-RC1, 5.6	Resolved	07/06/12
↓ NXP-8168	Marketplace package for BIRT	MP 2.1: http://hg.nuxeo.org/marketplace/birt-reporting/rev/4fcc402d6a96	Packaging	5.6-RC1, 5.6	Resolved	13/12/11
↓ NXP-9486	nuxeo-platform-seam-debug bundle should be included only in SDK	For {{5.5}}, in hot-fix remove the {{nuxeo-platform-seam-debug}} from the bundles directory.	Packaging	5.5.0-HF09, 5.6-RC1, 5.6	Resolved	12/06/12
↑ NXP-8247	optimize publication state queries	Document publishing state look-up is now based on ACL by default. You can select the task based look-up by contributing a new factory to the publisher service. That factory will sub-class the org.nuxeo.ecm.platform.publisher.task.CoreProxyWithWorkflowFactory and initialize the field lookupState to an instance of class org.nuxeo.ecm.platform.publisher.task.LookupStateByTask. If needed, you can select the state look-up strategy when you're requesting a publication tree org.nuxeo.ecm.platform.publisher.api.PublisherService.getPublicationTree by setting the property 'stateLookup' in the parameter map to 'byACL' or 'byTask'. The corresponding constants are defined in CoreProxyWithWorkflowFactory.	Publishing	5.4.2-HF15 5.5.0-HF01, 5.6-RC1, 5.6	Resolved	29/12/11
↓ NXP-8875	Allow runtime component name aliasing	A component can now specify <alias> names: <component name="com.example.comp.newfoo"> <alias>com.example.comp.oldfoo</alias> <alias>com.example.comp.veryoldfoo</alias> ... </component>	Runtime	5.6-RC1, 5.6	Resolved	16/02/12
↓ NXP-9316	wrong evaluation of ignore directives in non reloadable marketplace packages	Windows users: hand install the attached new launcher version for your platform (replace %NUXEO_HOME%\bin\nuxeo-launcher.jar)	Runtime	5.4.2-HF22 5.5.0-HF07, 5.6-RC1, 5.6	Resolved	09/05/12
↓ NXP-9546	Add a JUnit runner for executing parameterized tests suites	New JUnit4 runner: org.nuxeo.runtime.test.runner.ParameterizedSuite	Runtime, Tests	5.6-RC1, 5.6	Resolved	19/06/12
↑ NXP-8906	Allow DATE-based comparisons in NXQL	Now it's possible to make queries like: SELECT * FROM Document WHERE DATE(dc:modified) = DATE '2012-02-22'; This can be efficient only if the underlying database has a specialized index on the column. For PostgreSQL, the index must be added as: CREATE INDEX dc_modified_date_idx ON dublincore (DATE(modified))	Core SQL Storage ,Search / Query	5.4.2-HF18 5.5.0-HF04, 5.6-RC1, 5.6	Resolved	22/02/12
↓ NXP-9035	Allow user registration to have more than one configuration	User registration configuration should now use a name (by default is 'default_registration')	Social Collaboration	5.6-RC1, 5.6	Resolved	14/03/12
↓ NXP-9058	Move nuxeo-activity in its own repository	groupidp for nuxeo-activity has changed from org.nuxeo.ecm.social to org.nuxeo.activity.	Activity ,Social Collaboration	5.6-RC1, 5.6	Resolved	16/03/12
↓ NXP-9169	Use UserRegistration module in Social Collab	org.nuxeo.ecm.social.workspace.service.DefaultSubscriptionRequestHandler, org.nuxeo.ecm.social.workspace.service.SocialWorkspaceEmailNotifier and corresponding Actions class will be marked as deprecated and not used.	Social Collaboration	5.6-RC1, 5.6	Resolved	04/04/12
↓ NXP-9537	Fix remaining bugs on gadget Document Library	description is not clear enough for letting this ticket open	Social Collaboration	5.6	Resolved	18/06/12

PKey	Summary	Upgrade notes	Components	Fix Version/s	Status	Created
↓ NXP-9714	Rating > Missing label		Social Collaboration	5.6-RC2, 5.6	Resolved	17/07/12
↓ NXP-8623	Make it possible to run functional tests in Chrome	upgraded selenium-server version to 2.16.1	Tests	5.6-RC1, 5.6	Resolved	13/01/12
↓ NXP-9139	Upgrade to jmock2-junit4	<p>Tests depending on Nuxeo test cases (mostly NXRuntimeTestCase and SQLRepositoryTestCase) should be upgraded to junit4-style:</p> <ul style="list-style-type: none"> - don't extend TestCase - @Override anything void setUp should be replaced by @Before public void setUp - @Override anything void tearDown should be replaced by @After public void tearDown - all test methods (public void test*) should be annotated with @Test <p>The following shouldn't be referenced anywhere anymore:</p> <ul style="list-style-type: none"> - junit.framework - 'extends TestCase' 	Tests	5.6-RC1, 5.6	Resolved	31/03/12
↑ NXP-8733	Correctly escape command line parameters	<p>The parameters given to a command line should match the following regexp: <code>{{[a-zA-Z_0-9-_%:\ \]+}}</code></p> <p>There is no need to quote the file path or the parameters in the <code>{{parameterString}}</code>, everything is handled by the <code>{{AbstractExecutor}}</code> class.</p> <p>The contributions and classes are updated to remove <code>{{}}</code> and to use temporary files without special characters.</p>	Transforms / Preview	5.5.0-HF04, 5.6-RC1, 5.6	Resolved	26/01/12
↓ NXP-9531	Make XMap natively manage Enum	Added default Enum (de)serialization in XMap using Enum.name() and Enum.valueOf(String value)	Utils	5.6-RC1, 5.6	Resolved	15/06/12
↓ NXP-8194	set tx timeout from an http header	<p>New methods:</p> <ul style="list-style-type: none"> - TransactionHelper.startTransaction(timeout): starts a transaction with the given timeout. - ServletHelper.startTransaction(HttpServletRequest): starts a transaction with the timeout given by the Nuxeo-Transaction-Timeout header of the request. <p>For tests, new feature:</p> <ul style="list-style-type: none"> - JettyTransactionalFeature: manages the transaction manager and connection factory binding in the jetty naming. 	Web Foundations	5.5.0-HF01, 5.6-RC1, 5.6	Resolved	19/12/11
↓ NXP-7793	Add a content view widget type	widget template using content_view_widget.html has been removed, the widget with type "contentViewWithForms" should be used instead.	Web UI	5.6-RC1, 5.6	Resolved	28/10/11
↓ NXP-9048	Fix locale detection by JSF components when switching locale	if startupHelper was customized, need to switch locale calling restHelper#setLocaleString instead of localeSelector#setLocaleString	Web UI	5.4.2-HF19, 5.5.0-HF05, 5.6-RC1, 5.6	Resolved	15/03/12
↓ NXP-9052	Make page provider maxPageSize default value configurable with a runtime property	New property: nuxeo.pageprovider.default-max-page-size (100 by default, 0 means no limit)	Configuration, Web UI	5.4.2-HF20, 5.5.0-HF06, 5.6-RC1, 5.6	Resolved	15/03/12
↓ NXP-9089	Improve actions to support different displays for a single category	Added a type attribute to action definition, as well as custom properties, with a generic template to display actions depending on their type + compatibility extension point to add a type to all actions missing it when in a given category.	Web UI	5.6-RC1, 5.6	Resolved	21/03/12
↓ NXP-9118	Allow version selection and action contribution to the Archived versions sub-tab	<p>* VersionedActions: change List<VersionModel> getVersionList() to List<PageSelection<VersionModel>> getVersionList(), add #getCanRemoveSelectedArchivedVersions(), add #removeSelectedArchivedVersions(), add #restoreToVersion(), add #viewArchivedVersion(), add #getSelectedVersionId(), add #setSelectedVersionId(String selectedVersionId)</p> <p>* VersionedActionsBean: change List<VersionModel> versionModelList to List<PageSelection<VersionModel>> versionModelList, add #documentsListsManager</p> <p>* documentslists-contrib.xml: add CURRENT_SELECTION_VERSIONS</p> <p>* DocumentListingActionsBean: add #documentManager, add #checkCurrentDocAndProcessVersionSelectRow</p> <p>* ConversationDocumentsListsManager: add #refreshListsOnDocumentSelectionChanged, add #refreshLists(String eventName, DocumentModel selectedDocument)</p> <p>* DocumentsListsManager: add #CURRENT_VERSION_SELECTION</p>	Web UI	5.6-RC1, 5.6	Resolved	28/03/12
↓ NXP-9404	Allow to check a filter without actions and to retrieve a filtered action by id instead of category	Added API on ActionManager: #checkFilter(filterId, actionContext) and #getAction(actionId, actionContext, hideUnavailableAction) and similar methods on webActions seam component	Web UI	5.6-RC1, 5.6	Resolved	01/06/12
↓ NXP-9868	Improve document edition API on Seam components	Added DocumentActions#updateDocument(doc, bool restoreCurrentTabs)	Web UI	5.6	Resolved	10/08/12
↓ NXP-9891	Allow setting action properties programmatically	Added Action#setProperties	Web UI	5.6	Resolved	17/08/12
↓ NXP-8840	Allow instantiation of a LayoutRowDefinitionImpl with a category and a widget name	A new constructor is available: public LayoutRowDefinitionImpl(String name, String widget, String category)	Web Widgets	5.6-RC1, 5.6	Resolved	09/02/12
↓ NXP-8939	Add a contextual information to know a document was edited through WebDAV	New information available in document contextData variable : source-edit accessible with docMode.getContextData("source-edit")	WebDAV / WSS	5.4.2-HF18, 5.5.0-HF04, 5.6-RC1, 5.6	Resolved	28/02/12
↑ NXP-8552	Fix crash when approving workflow task	<p>* TaskProvider: add the #endTask method.</p> <p>* TaskService: change the return type from void to String for the 3 methods #acceptTask, #rejectTask, #endTask. They now return the name of the Seam event to raise after execution. The unused #notifyEventListeners method was removed.</p> <p>* TaskServiceImpl: add the DEFAULT_TASK_PROVIDER constant for the default task provider name.</p> <p>* JBPMTaskWrapper: add the JBPM_TASK_PROVIDER constant for the JBPM task provider name.</p> <p>* Task: add the TASK_PROVIDER_KEY constant for the task provider variable key.</p> <p>* JBPMDocTaskProvider: add the WORKFLOW_REJECT_TRANSITION constant for the workflow "reject" transition.</p> <p>* Add 3 classes: AbandonProcessUnrestricted, EndProcessUnrestricted,</p>	Workflow	5.5.0-HF05, 5.6-RC1, 5.6	Resolved	04/01/12

PKey	Summary	Upgrade notes	Components	Fix Version/s	Status	Created
		TaskEventNotificationHelper to externalize and factorize their logic.				
↓ NXP-9832	Allow displaying tasks actions in content views	selectionActions#onClick can not lookup components up using a given level (using int param lookupLevel or string field lookupLevelValue) content_view.xhtml template accepts more templating slots for actions and after the main documents form.	Workflow	5.6	Resolved	02/08/12
↑ NXP-9991	Routes model reload reinit repo too early on hot reload	Hot reload triggers a repository init too early due to being called on "flush" instead of "reload". The consequence is that the repo doesn't see any type defined in the plugin that's deactivated before being reactivated.	Workflow	5.6	Resolved	30/08/12
↓ NXP-8235	Use recommended Oracle JDBC driver class	Any custom nuxeo.xml or server.xml or nuxeo.defaults in the templates/, or a customized nuxeo.db.driver in nuxeo.properties should use the new Oracle-recommended driver class "oracle.jdbc.OracleDriver" instead of the old "oracle.jdbc.driver.OracleDriver".	5.6-RC1	, 5.6	Resolved	27/12/11
↓ NXP-8620	remove imported naming implementation from nuxeo common	- org.nuxeo.common.jndi package is merged into org.nuxeo.runtime.itajca - calls to NamingContextFactory.install should be replaced by calls to org.nuxeo.runtime.itajca.NuxeoContainer.install if no tx/resource management needed org.nuxeo.runtime.itajca.NuxeoContainer.installNaming if not - calls to NamingContextFactory.revertSetAsInitialContext should be replaced by calls to org.nuxeo.runtime.itajca.NuxeoContainer.uninstall	5.6-RC1	, 5.6	Resolved	13/01/12
↑ NXP-8622	Update copyright to 2012 in footer	customized footer and login pages should fill the variable with year "2012" if they're using the localized message "label.login.copyright"	5.6-RC1	, 5.6	Resolved	13/01/12
↓ NXP-8804	NXP-8792 Splitting user-registration into 2 modules	user-platform-registration is now missing. Module dependencies are now: - user-platform-registration-core: Service, Descriptor, etc. - user-platform-registration-web: implementation with content views, actions, default templates, etc.	5.6-RC1	, 5.6	Resolved	07/02/12
↓ NXP-8842	Make test core feature compatible with transactional feature	Core feature is providing a guice scope for a better handling of the session reset. In tests, features that want to configure a service provider should now provide a org.nuxeo.runtime.test.runner.ServiceProvider instead of com.google.inject.Provider. This let the feature being able to override the default scope binding.	5.5.0-HF03	,5.6-RC1 , 5.6	Resolved	10/02/12
↓ NXP-8992	Extend rendition system	Some changes have been done on the API - List<RenditionDefinition> getAvailableRenditionDefinitions(); + List<RenditionDefinition> getDeclaredRenditionDefinitions(); and - DocumentRef render(DocumentModel sourceDocument,String renditionDefinitionName) throws RenditionException; + DocumentRef storeRendition(DocumentModel sourceDocument, String renditionDefinitionName) throws RenditionException;	5.6-RC1	, 5.6	Resolved	05/03/12
↓ NXP-9025	Make it possible to update virtual groups of a user from the ComputedGroupsService	New method added on ComputedGroupService: void updateGroupsForUser(NuxeoPrincipalImpl nuxeoPrincipal)	5.5.0-HF05	,5.6-RC1 , 5.6	Resolved	12/03/12
↑ NXP-9092	propagated security context leaks in JBoss	Add in the definition of the authentication plugin <needStartingURLSaving>true</needStartingURLSaving>	5.4.2-HF21	,5.5.0-HF06 ,5.6-RC1 , 5.6	Resolved	22/03/12
↓ NXP-9334	Add to FileUtils a readBytes(InputStream in, boolean closeInputStream) method that allows not to close the InputStream (useful for ZipInputStream)	Added FileUtils#readBytes(InputStream in, boolean closeInputStream)	5.6-RC1	, 5.6	Resolved	15/05/12
↓ NXP-9382	Fix image widgets display under IE	img tag is not rendered anymore when src value is empty	5.5.0-HF08	,5.6-RC1 , 5.6	Resolved	28/05/12
↓ NXP-9677	Fix hot reload of action filters	use ContributionFragmentRegistry#removeContribution(contrib, true) when needing to use the "equals" method on contribution	5.6-RC3	, 5.6	Resolved	15/07/12
↓ NXP-9874	Error at startup about property "nuxeo.server.https.keystoreFile" when upgrading to 5.6	https support requires more properties to be filled now. do not configure any of the https properties if you do not use https anyway, or fill the properties the startup complains about. The properties to define are: - nuxeo.server.https.port=443 - nuxeo.server.https.keystoreFile=/path/to/keystore - nuxeo.server.https.keystorePass=password - nuxeo.url=https://localhost/nuxeo	5.6		Resolved	13/08/12