

UpgradeNotes571 (Nuxeo Issue Tracker)

JQL Query: project = "Nuxeo Enterprise Platform" AND resolution = Fixed AND fixVersion = "5.7.1" AND ("Impact type" = "API change" OR "Upgrade notes" is not EMPTY) ORDER BY component ASC

Sorted by: Component/s ascending

1-70 of 70 as at: 19/06/13 17:33

P	Key	Summary	Upgrade notes	Components	Fix Version/s	Status	Created
+	NXP-11129	Check Studio packages compatibility with current Nuxeo version and configuration	Added framework property <code>{{studio.snapshot.disablePkgValidation}}</code> to disable this validation in case of problem	Admin Center, DAM, Packaging	5.7.1	Resolved	01/03/13
+	NXP-10886	Fix navigation in history for proxies and versions	Need to implement the need method <code>hasChangedParameters(Object[])</code> from <code>PageProvider</code> interface	Audit	5.7.1	Resolved	29/01/13
+	NXP-11403	org.nuxeo.ecm.automation.OperationException should not be mapped to HTTP 500	Kept <code>org.nuxeo.ecm.automation.OperationException</code> mapping with HTTP 500 waiting for NXP-11094. Made Drive wrap <code>java.lang.UnsupportedOperationException</code> into a new <code>org.nuxeo.ecm.automation.InvalidOperationException</code> , itself mapped with HTTP 400. Also, made the <code>org.nuxeo.ecm.automation.server.jaxrs.ExceptionHandler</code> map <code>org.nuxeo.ecm.core.api.ClientException</code> with no root cause to HTTP 400.	Automation	5.7.1	Resolved	11/04/13
+	NXP-10306	Automation client: add an API to get a session using a token	Added: - <code>AutomationClient#getSession(String token)</code> - <code>AutomationClient#getSession(TokenCallback cb)</code>	Automation	5.6.0-HF10, 5.7.1	Resolved	15/10/12
+	NXP-10209	Automation - SendMail: allow to not rollback the automation chain in case of an Exception	New boolean optional parameter: <code>rollbackOnError</code> . Default value = true to keep the previous behavior.	Automation	5.6.0-HF02, 5.7.1	Resolved	02/10/12
+	NXP-10092	Automation: add a generic operation similar to GetSelectedDocuments with a parameter for the selection list name	Added <code>GetDocumentsFromSelectionList</code> operation.	Automation	5.7.1	Resolved	13/09/12
+	NXP-8630	Fix inverted event handler EL expression evaluation	Use the new parameter "condition" instead of "expression" when migrating event handlers	Automation	5.7.1	Resolved	30/12/11
+	NXP-11477	Move Operation and Script feature from Presales Toolkit into the Nuxeo Platform	Add following new Operations : - <code>AddEntryToMultiValuedProperty</code> - <code>CreateProxyLive</code> - <code>GetLiveDocument</code> - <code>RemoveEntryOfMultiValuedProperty</code> Add the following new functions into the Fn Object: - <code>concatenateIntoList</code> - <code>concatenateValuesAsNewList</code>	Automation	5.7.1	Resolved	26/04/13
+	NXP-11503	Automation requests with valid credentials but that lacks some permissions on a doc should be mapped to HTTP 403 instead of 401	To preserve backward compat for 5.6 compatible clients, the hotfix will not change the behavior of automation server by default unless explicitly stated in <code>{{nuxeo.conf}}</code> with the following line: <code>org.nuxeo.ecm.automation.server.permission.httppcode=403</code> In 5.7, authorization exceptions are mapped by default to 403.	Automation, Nuxeo Drive	5.6.0-HF17, 5.7.1	Resolved	02/05/13
+	NXP-11536	Add version label into the Document/JSON Export from Automation Rest Request	Add <code>VersionLabel</code> into the JSON export and Add new <code>Getter</code> into the <code>org.nuxeo.ecm.automation.client.model.Document</code> to get this information	Automation	5.6.0-HF17, 5.7.1	Resolved	15/05/13
+	NXP-10780	Allow save without auto-checkout	To disable auto-checkout before a document save, do: <code>doc.putContextData(VersingService.DISABLE_AUTO_CHECKOUT, Boolean.TRUE);</code> <code>doc = session.saveDocument(doc);</code> Make sure that this is done only for changes that do not correspond to things that the user would like to see versioned.	Core	5.6.0-HF09, 5.7.1	Resolved	10/01/13
+	NXP-10679	WorkManager should allow Work execution to be delayed after the transaction commit	New <code>WorkManager</code> APIs: - <code>void schedule(Work work, boolean afterCommit)</code> - <code>void schedule(Work work, Scheduling scheduling, boolean afterCommit)</code>	Core	5.7.1	Resolved	19/12/12
+	NXP-10668	Allow WorkManager scheduling to use a priority queue	When specifying the configuration for a Work queue, you can add: <code><usePriority>true</usePriority></code> to make the queue be a <code>PriorityQueue</code> . In this case the Work instances inserted in the queue must be Comparable with each other.	Core	5.7.1	Resolved	17/12/12
+	NXP-10481	Provide destination folder in ABOUT_TO_XXX events	Should not impact existing code	Core	5.6.0-HF06, 5.7.1	Resolved	15/11/12
+	NXP-11564	Add version label into the detach action in DocumentModelImpl	Add version label into the <code>documentModel.detach</code> method	Core	5.6.0-HF18, 5.7.1	Resolved	20/05/13
+	NXP-10053	NXP-10018 Extend usage of XSD maxOccurs attribute to handle List definition	h3. Background info Until 5.6 the <code>{{maxOccurs}}</code> attribute of the <code>{{xs:element}}</code> was not parsed correctly in all cases. Normally, an <code>{{xs:element}}</code> with a <code>{{maxOccurs}} > 1</code> should be seen as a List. Until 5.6 it was only true when the <code>{{xs:sequence}}</code> had just one element. The problem is visible for complex types declaring several fields : {code} <code><xs:complexType name="complexWithSubList"> <xs:sequence> <xs:element name="fieldA" type="xs:string" /> <xs:element name="items" type="xs:string" minOccurs="0" maxOccurs="unbounded" /> </xs:sequence> </xs:complexType> {code}</code> Here in 5.6, the field "items" won't be considered as a List. In 5.7, the parsing will be ok and items will be List<String>. Unfortunately, until 5.6, probably because of bad copy/past a lot of schema were wrongly declared. {code} <code><xs:complexType name="relatedtextresource"> <xs:sequence> <xs:element name="relatedtextid" type="xs:string" minOccurs="0" maxOccurs="unbound" /> <xs:element name="relatedtext" type="xs:string" minOccurs="0" maxOccurs="unbound" /> </xs:sequence> </xs:complexType> {code}</code> In 5.6 this <code>{{relatedtextresource}}</code> was seen as a Map<String, String> with 2 keys, <code>{{relatedtextid}}</code> and <code>{{relatedtext}}</code> . In 5.7 this same item would be correctly parsed as Map<String, List<String>> with 2 keys, <code>{{relatedtextid}}</code> and <code>{{relatedtext}}</code> . All Nuxeo "built-in" schema where updated, like the relatedText one : https://github.com/nuxeo/nuxeo-core/commit/efad46527cd06f0cd0ec8cb4f55595016c2a408	Core	5.7.1	Resolved	10/09/12

P	Key	Summary	Upgrade notes	Components	Fix Version/s	Status	Created
			<p>h3. What should be checked</p> <p>Inside your XSD schemas, check that the declaration of complex Type that have more than one field don't use maxOccurs="unbound" without any reasons.</p>				
↑	NXP-11562	Allow attaching schemas to proxies	<p>To define one or more schemas that should be available on all proxies, use this kind of extension point:</p> <pre><extension target="org.nuxeo.ecm.core.schema.TypeService" point="doctype"> <proxies> <schema name="myschema1"/> <schema name="myschema2"/> </proxies> </extension></pre>	Core, Core SQL Storage	5.7.1	Resolved	20/05/13
↓	NXP-11370	Flag to globally disable proxies	<p>To disable proxies, add to the repository configuration:</p> <pre><proxies enabled="false" /></pre>	Core, Core SQL Storage	5.6.0-HF15, 5.7.1	Resolved	08/04/13
↓	NXP-10308	Single-datasource mode to work without XA	<p>To activate single-datasource mode (which is the default since Nuxeo 5.7.1), define the variable:</p> <pre>nuxeo.db.singleDataSource=jdbc/NuxeoDS</pre> <p>By default this is defined from templates/common-base/nuxeo.defaults.</p> <p>To disable it (which you MUST DO if you use several repositories), just use:</p> <pre>nuxeo.db.singleDataSource=</pre> <p>The datasource name can of course be different than jdbc/NuxeoDS, but it must be a valid datasource already defined elsewhere.</p> <p>In addition, the maximum pool size for the datasource must be enough for all the VCS connections, which means that you must have</p> <pre>nuxeo.db.max-pool-size ≥ nuxeo.vcs.max-pool-size + 2</pre> <p>(The + 2 comes from two reserved connections for the VCS lock manager and the cluster node handler.)</p>	Core, Core SQL Storage, Directory	5.7.1	Resolved	15/10/12
↑	NXP-10321	lazy binaries not serializable		Core SQL Storage	5.6.0-HF02, 5.7.1	Resolved	17/10/12
↓	NXP-10235	Add missing indexes to scale	<p>For customer that have put an index on fulltext jobid you need to remove it because the name has changed:</p> <pre>DROP INDEX JOBID_ID_IDX;</pre>	Core SQL Storage	5.5.0-HF15, 5.6.0-HF02, 5.7.1	Resolved	04/10/12
↑	NXP-10219	Support Microsoft's JDBC driver for SQL Server	<p>To support XA using the Microsoft JDBC driver, some setup has to be done in the SQL Server itself. It is "NECESSARY" to follow the Configuration Instructions listed at http://msdn.microsoft.com/en-us/library/aa342335(v=sql.105).aspx</p> <p>In particular, after the configuration, note that you must add your database user ('nuxeo' in this example) to proper role in order for him to execute XA statements:</p> <pre>USE master EXEC sp_grantdbaccess 'nuxeo', 'nuxeo' EXEC sp_addrolemember [SqlJDBCXAUser], 'nuxeo'</pre> <p>Some screenshots for the first part are visible at http://www.sqlserver-dba.com/2011/12/enable-xa-transactions-for-sql-server.html</p>	Core SQL Storage	5.6.0-HF02, 5.7.1	Resolved	03/10/12
↓	NXP-10210	Improve pathOptimizations on Oracle	<p>When upgrading from 5.6 to 5.7 and using Oracle, you need to drop the ancestors table, see the ticket for more information.</p>	Core SQL Storage	5.4.2-HF29, 5.5.0-HF16, 5.6.0-HF04, 5.7.1	Resolved	02/10/12
↓	NXP-9975	Use PostgreSQL unlogged table for cache tables	<p>To take effect on existing instance, acl_user, acl_user_map and aclr_modified tables need to be dropped.</p>	Core SQL Storage	5.7.1	Resolved	29/08/12
↑	NXP-4147	VCS: allow queries about tags using NXQL	<p>Examples from the doc:</p> <pre>SELECT * FROM Document WHERE ecm:tag = 'tag1' SELECT * FROM Document WHERE ecm:tag IN ('tag1', 'tag2') -- documents with either tag SELECT * FROM Document WHERE ecm:tag" = 'tag1' AND ecm:tag" = 'tag2' -- documents with both tags SELECT ecm:tag FROM Document WHERE dc:title = 'something' -- with queryAndFetch SELECT ecm:tag FROM Document WHERE ecm:tag LIKE 'abc%' -- with queryAndFetch SELECT ecm:tag"1 FROM Document WHERE ecm:tag"1 LIKE 'abc%' AND ecm:tag"2 = 'tag1' SELECT ecm:tag FROM Document WHERE ecm:tag LIKE 'abc%' AND ecm:tag" = 'tag1' -- simpler version of above</pre>	Core SQL Storage	5.7.1	Resolved	07/10/09
↓	NXP-11543	Allow execution of client-specific SQL at database init	<p>In the repository configuration use <code><sqlInitFile>myconf.sql.txt</sqlInitFile></code> to read one or more additional files.</p> <p>The format of the file is documented at http://doc.nuxeo.com/x/hwQz.</p>	Core SQL Storage	5.7.1	Resolved	15/05/13
↑	NXP-11335	Soft delete for PostgreSQL, SQL Server and Oracle	<p>To enable soft-delete, add to the repository configuration:</p> <pre><softDelete enabled="true" /></pre>	Core SQL Storage	5.7.1	Resolved	30/03/13
↓	NXP-4803	VCS with PostgreSQL should use UUID type for doc id field	<p>To activate, in the repository config, add:</p> <pre><idType>uuid</idType></pre>	Core SQL Storage	5.7.1	Resolved	26/02/10
↓	NXP-11056	NXP-11080 Do not rely anymore on 'HiddenInFacetedSearch' facet	<p>The saved searches are not anymore displayed in the "Saved searches" folder on the Personal workspace of the users.</p> <p>However they are still inside that folder (now empty in the UI).</p> <p>In Home / Saved searches / Faceted searches, there is a button "Migrate saved searches" to migrate the old saved searches stored inside the "Saved searches" folder. After doing that, the "Saved searches" folder can be safely deleted.</p>	DAM, Faceted Search	5.7.1	Resolved	22/02/13
↓	NXP-8732	Add Drag & drop in DAM domain	<p>upgrade from nuxeo DM 5.4.2 to nuxeo platform 5.5 with DM and DAM module.</p>	DAM	5.7.1	Closed	25/01/12
↓	NXP-11061	NXP-11168 Improve tags and tagging widgets	<p>To keep the old behavior about re-rendering on the 'summary_current_document_tagging' widget, the 'ajaxReRender' property need to be defined on the widget instance.</p> <p>To display the label, the 'handleLabels' control needs to be added to the widget definition.</p> <pre><widget name="summary_current_document_tagging"> ... <controls mode="any"> ... <control name="handleLabels">true</control> </controls> <properties mode="any"> <property name="ajaxReRender">MultiTreeView</property> </properties></pre>	DAM, Faceted Search	5.7.1	Resolved	22/02/13

P	Key	Summary	Upgrade notes	Components	Fix Version/s	Status	Created
			... </widget>				
↓	NXP-10669	Wrap LDAP calls to retry the request if LDAP is temporary unavailable	A new attribute <code>{{retries}}</code> can be set when defining LDAP server to indicates how many times the request is sent to LDAP before considering the service is really unavailable <server name="foo"> <retries>5</retries> </server>	Directory	5.4.2-HF31, 5.5.0-HF18, 5.6.0-HF07, 5.7.1	Resolved	18/12/12
↓	NXP-10551	Add a property to make inverse reference read only	A new attribute is available when defining an InverseReference: add <code>readOnly="true"</code> to skip any update of the directory defined as a target of the inverse reference. Example : <inverseReference field="parentGroups" directory="groupDirectoryMulti" dualReferenceField="subGroups" readOnly="true"/>	Directory	5.4.2-HF30, 5.5.0-HF17, 5.6.0-HF06, 5.7.1	Resolved	27/11/12
↓	NXP-10701	Allow FileManager to save version after creation	Example (default is false): <extension target="org.nuxeo.ecm.platform.filemanager.service.FileManagerService" point="versioning"> <versioning> <defaultVersioningOption>MAJOR</defaultVersioningOption> <versionAfterAdd>true</versionAfterAdd> </versioning> </extension>	Importer	5.6.0-HF09, 5.7.1	Resolved	27/12/12
↓	NXP-10576	Provide a new extension point to choose the default increment option for versioning	New extension point "versioning" for FileManager service. Example (default is MINOR): <extension target="org.nuxeo.ecm.platform.filemanager.service.FileManagerService" point="versioning"> <versioning> <defaultVersioningOption>MAJOR</defaultVersioningOption> </versioning> </extension>	Importer	5.6.0-HF06, 5.7.1	Resolved	30/11/12
↓	NXP-10060	Importer: plug a method call on node creation error and allow to continue global import task	Added ImporterDocumentModelFactory#processFolderishNodeCreationError(CoreSession session, DocumentModel parent, SourceNode node) and ImporterDocumentModelFactory#processLeafNodeCreationError(CoreSession session, DocumentModel parent, SourceNode node) + add default implementation in AbstractDocumentModelFactory	Importer	5.7.1	Resolved	10/09/12
↓	NXP-10051	Avoid WARN at JAX-RS app init	In both AbstractImporterExecutor and AbstractJaxRsImporterExecutor: public void kill() becomes public String kill()	Importer	5.7.1	Resolved	08/09/12
↓	NXP-10006	importer should use path segment service for naming documents	If needed, the older naming rules can be selected by setting the 'nuxeo.importer.compatFilenames' to 'true'.	Importer	5.5.0-HF14, 5.6.0-HF01, 5.7.1	Resolved	03/09/12
↑	NXP-10224	Fix configuration templates deployment order	Prior to that fix, configuration templates missing a nuxeo.defaults file may sometimes be included. That's no more the case: in order to be included, a template must have a nuxeo.defaults file.	Launcher	5.6.0-HF03, 5.7.1	Resolved	03/10/12
↓	NXP-10435	Add fine grained form control on some widget types	Widgets now accept "control" properties by mode to control if a form is displayed around them and if they handle their label	Layouts / Widgets	5.7.1	Resolved	08/11/12
↓	NXP-10184	Fix user/group suggestion widget types	singleUserSuggestion now displays a link to the user/group by default on view, add property "displayAction" with value "nothing" to get back the old behaviour. It also displays a user/group icon by default, use property "hideIcon" with value "true" to get back the old behaviour.	Layouts / Widgets	5.4.2-HF29, 5.5.0-HF15, 5.6.0-HF02, 5.7.1	Resolved	26/09/12
↑	NXP-10948	Can't change label of workflow summary widget	To display the label, the 'handleLabels' control needs to be added to the widget definition: <widget name="summary_current_document_single_tasks" type="summary_current_document_single_tasks"> <controls mode="any"> ... <control name="handleLabels">true</control> </controls> </widget>	Layouts / Widgets	5.7.1	Resolved	27/08/12
↓	NXP-11566	Allow resetting some JSF components state when using ajax	JSF action listener <code>#(jsfResetActions.resetComponents)</code> can be used in actions that need to reset all components in the same JSF naming container	Layouts / Widgets	5.6.0-HF18, 5.7.1	Resolved	20/05/13
↓	NXP-10179	Allow to use "Compatible Classic" mode for Freemarker rendering	Classic Compatible mode is now set to true to render freemarker template for notifications	Notifications	5.6.0-HF02, 5.7.1	Resolved	26/09/12
↑	NXP-11440	Long running transactions might cause Nuxeo Drive to miss some document updates	A new column <code>{{log_date}}</code> is introduced in the <code>{{(npx_log_date}}</code> column. By default the <code>log_date</code> of the old events will be null which should not be a problem. It is possible to set the value of the <code>{{(log_date = null}}</code> rows to <code>{{(log_event_date}}</code> instead.	Nuxeo Drive	5.6.0-HF16, 5.7.1	Resolved	19/04/13
↓	NXP-10350	Make relation graphs use core directly (not Jena) (except annotations)	If you wish to keep using Jena for some of the relation graphs, use the following contributions: <require>org.nuxeo.ecm.platform.relations.default.graph</require> <extension target="org.nuxeo.ecm.platform.relations.services.RelationService" point="graphs"> <graph name="default" type="jena-or-core"> <option name="doctype">DefaultRelation</option> <option name="backend">sql</option> <option name="databaseType"> \${org.nuxeo.ecm.sql.jena.databaseType} </option> <option name="datasource">jdbc/nxrelations-default-jena</option> <option name="databaseDoCompressUri">>false</option> <namespaces> <namespace name="rdf"> http://www.w3.org/1999/02/22-rdf-syntax-ns# </namespace> <namespace name="dcterms">http://purl.org/dc/terms/</namespace> <namespace name="nuxeo">http://www.nuxeo.org/document/uid/</namespace> </namespaces> </graph> </extension> <require>org.nuxeo.ecm.platform.comment.service.default.graph</require> <extension target="org.nuxeo.ecm.platform.relations.services.RelationService" point="graphs"> <graph name="documentComments" type="jena-or-core"> <option name="doctype">CommentRelation</option> <option name="backend">sql</option> <option name="databaseType"> \${org.nuxeo.ecm.sql.jena.databaseType} </option> <option name="datasource">jdbc/comment-relations</option> <option name="databaseDoCompressUri">>false</option>	Relations	5.7.1	Resolved	19/10/12

P	Key	Summary	Upgrade notes	Components	Fix Version/s	Status	Created
			<pre> <namespaces> <namespace name="comment">http://www.nuxeo.org/comments/uid&lt;/namespace> <namespace name="isCommentFor"> http://www.nuxeo.org/predicates/isCommentFor </namespace> <namespace name="document">http://www.nuxeo.org/document/uid&lt;/namespace> </namespaces> </graph> </extension> <require>org.nuxeo.ecm.platform.publisher.relations.contrib</require> <extension target="org.nuxeo.ecm.platform.relations.services.RelationService" point="graphs"> <graph name="publication" type="jena-or-core"> <option name="doctype">PublicationRelation</option> <option name="backend">sql</option> <option name="databaseType"> \${org.nuxeo.ecm.sql.jena.databaseType} </option> <option name="datasource">java://nxrelations-default-jena</option> </namespaces> <namespace name="rdf"> http://www.w3.org/1999/02/22-rdf-syntax-ns# </namespace> <namespace name="dcterms">http://purl.org/dc/terms/1.1/&lt;/namespace> <namespace name="nuxeo">http://www.nuxeo.org/document/uid&lt;/namespace> <namespace name="pTree">http://www.nuxeo.org/publication/tree&lt;/namespace> </namespaces> </graph> </extension> </pre>				
↓	NXP-10340	NXQL fails on backslash at end of string	<p>NXQL incompatibility: \ used to mean \ but now means \</p> <p>i.e., two consecutive backslashes inside a strings were previously interpreted as two backslashes. Now they are interpreted as only one backslash.</p> <p>There are two new helper methods to do string escaping:</p> <ul style="list-style-type: none"> - NXQL.escapeString - NXQL.escapeStringInliner 	Search / Query	5.6.0-HF08, 5.7.1	Resolved	18/10/12
↓	NXP-10155	Allow forcing refresh of content views on rendering	<p>When content view cache is set to 0, the content view is cached anyhow with only one instance per user (and a static cache key), when rendering the content view again, the associated page provider is refreshed.</p>	Search / Query	5.6.0-HF02, 5.7.1	Resolved	20/09/12
↑	NXP-10268	Add a token based authentication module	<p>Added:</p> <ul style="list-style-type: none"> - TokenAuthenticationService - TokenAuthenticator - TokenAuthenticationServlet 	Security / Rights	5.6.0-HF10, 5.7.1	Resolved	08/10/12
↓	NXP-10152	let user manually synch documents between two server		Synchronization	5.6.0-HF01, 5.6.0-HF02, 5.7.1	Resolved	19/09/12
↓	NXP-10255	Make it easier to test Nuxeo with webdriver	<p>Added helper classes LayoutElement, WidgetElement...</p>	Tests	5.7.1	Resolved	08/10/12
↓	NXP-7672	Handle CSS3 format in theme styling files	<p>The flute CSS parser has now been replaced by phloc-css (https://code.google.com/p/phloc-css/)</p> <p>The following dependencies have been removed from the dependencyManagement of Nuxeo root pom:</p> <pre> <dependency> <groupId>org.milyn</groupId> <artifactId>milyn-magger</artifactId> <version>1.3.1-NXP-7750</version> <!-- removed duplicate batik classes --> </dependency> <dependency> <groupId>org.milyn</groupId> <artifactId>milyn-commons</artifactId> <version>1.3.1</version> </dependency> <dependency> <groupId>org.milyn</groupId> <artifactId>flute</artifactId> <version>1.3-gg2</version> </dependency> <dependency> <groupId>org.w3c</groupId> <artifactId>sac</artifactId> <version>1.3</version> <groupId>com.phloc</groupId> <artifactId>phloc-css</artifactId> <version>3.3.1</version> </dependency> </pre>	Themes	5.7.1	Resolved	10/10/11
↓	NXP-11199	Make the 'summary_current_document_comments' widget be able to handle its label	<p>To display the label, the 'handleLabels' control needs to be added to the widget definition:</p> <pre> <widget name="summary_current_document_comments" type="summary_current_document_comments"> <controls mode="any"> ... <control name="handleLabels">true</control> </controls> </widget> </pre>	Web Foundations	5.7.1	Resolved	08/03/13
↓	NXP-10954	Make the 'summary_current_document_states' widget be able to handle its label	<p>To display the label, the 'handleLabels' control needs to be added to the widget definition:</p> <pre> <widget name="summary_current_document_states" type="summary_current_document_states"> <controls mode="any"> ... <control name="handleLabels">true</control> </controls> </widget> </pre>	Web Foundations	5.7.1	Resolved	08/02/13
↓	NXP-10380	Remove global form around summary view	<p>Summary widgets that need a surrounding form have to specify that they need a surrounding form by adding the following control to their definition:</p> <pre> <controls mode="any"> <control name="addSurroundingForm">true</control> </controls> </pre> <p>Old summary layouts defined on document type for mode "summary" will not have a surrounding form. When using the mode "grid_summary", there will be no surrounding form.</p>	Web UI, Workflow	5.7.1	Resolved	29/10/12
↓	NXP-10694	Improve Timeout Management in Html5 DnD	<p>There are 3 timeouts (expressed in milliseconds) that are configurable server wide using system properties or nuxeo.conf entries:</p> <ul style="list-style-type: none"> - org.nuxeo.dnd.extendedmode.timeout (default 2000) defines after how long the drop zone switches to extended import mode with metadata. 	Web UI	5.6.0-HF08, 5.6.0-HF11, 5.7.1	Resolved	27/12/12

P	Key	Summary	Upgrade notes	Components	Fix Version/s	Status	Created
			- org.nuxeo.dnd.upload.timeout (default 30000) defines the timeout for the upload of a single file to the server (into a temporary storage). - org.nuxeo.dnd.exec.timeout (default 30000) defines the timeout for the execution, after all files have been uploaded, of the actual addition of the files to the document and related processing.				
↓	NXP-11217	NXP-11080 Move widgets and containers styles to a specific css	style named "grids_and_widgets" should be added to theme pages that need these styles	Web UI	5.7.1	Resolved	13/03/13
↑	NXP-10238	Use FileManager service to create appropriate document type through WebDAV	If the old behavior is absolutely needed, the following Nuxeo property can be set: nuxeo.webdav.always-create-file=true	WebDAV / WSS	5.6.0-HF12, 5.7.1	Resolved	04/10/12
↓	NXP-11408	Comments in the default serial workflow are not displayed in "Past tasks" view	Workflow enablement filter id has been temporarily changed from "filter@SerialDocumentReview" to "filter@wf@SerialDocumentReview", and included in 5.6.0-HF17, but this change will be reverted for 5.6.0-HF18	Workflow	5.6.0-HF17, 5.7.1	Resolved	12/04/13
↓	NXP-11419	Cannot restore content view with currentPage > 0	PageProviderService#getPageProvider API now take an additional DocumentModel parameter to represent the search document model		5.7.1	Resolved	16/04/13
↓	NXP-11345	Right audit matrix > non Folderish files audited			5.6.0-HF15, 5.7.1	Resolved	03/04/13
↓	NXP-10702	Provide auto-relogin feature on OpenSocial Dashboard	When the http session timeout on a dashboard page, touching one of the gadget will refresh it and will end up displaying the login form in the gadget iframe. We should provide a dedicated auth chain for OpenSocial gadget rendering fetching so that in case of an authenticated request it will return a custom page that can trigger the reload of the hosting page.		5.6.0-HF08, 5.7.1	Resolved	28/12/12
↓	NXP-10643	Allow nuxeo-diff to compare files statelessly	New method available: org.nuxeo.ecm.diff.web.DiffActionsBean#getContentDiffURL taking leftDocId and rightDocId		5.7.1	Resolved	13/12/12
↑	NXP-10921	Safari drag'n drop on Safari 6.0.2 doesn't work anymore	Mac OS Mountain Lion 10.8.2 Safari 6.0.2 (8536.26.17)		5.6.0-HF11, 5.7.1	Resolved	04/02/13
↓	NXP-10117	Allow UserWorkspace to built itself with a principal	org.nuxeo.ecm.platform.userworkspace.api.UserWorkspaceService#getUserPersonalWorkspace		5.7.1	Resolved	17/09/12
↓	NXP-11463	Update nuxeo dependency management following automation client changes	To get osgi versions of these dependencies, upgrades have been made: - javax.mail:mail upgrade from 1.4 to 1.4.5 - org.apache.httpcomponents versions upgrade to 4.2.4 from 4.2.3 Exclusions: - log4j:log4j, avalon-framework:avalon-framework, logkit:logkit exclusions from: javax.persistence:persistence-api - commons-logging:commons-logging, org.apache.httpcomponents:httpClient-cache exclusions from: org.apache.httpcomponents:httpClient		5.7.1	Resolved	24/04/13
↓	NXP-10793	Remove dash character from form names	JSF function nux:jsfTagIdEscape can now be used to sanitize ids fir JSF/Ajax		5.6.0-HF11, 5.7.1	Resolved	14/01/13
↓	NXP-10118	NXP-10078 Improve AutomationClient	- Added AbstractAutomationClient#setSharedRegistryExpirationDelay(long delay) to update the default delay set to 60 seconds. - Added HttpConnector#HttpConnector(HttpClient http, long httpConnectionTimeout) and HttpConnector#HttpConnector(HttpClient http, HttpContext ctx, long httpConnectionTimeout) to instantiate a new HttpConnector with an HTTP connection timeout. - Added HttpAutomationClient#HttpAutomationClient(String url, long httpConnectionTimeout) and HttpAutomationClient#HttpAutomationClient(String url, long httpConnectionTimeout, long asyncAwaitTerminationTimeout) to instantiate a new HttpAutomationClient with an HTTP connection timeout and a timeout for the wait of the asynchronous thread pool execution. - Added AsyncAutomationClient#AsyncAutomationClient(String url, long asyncAwaitTerminationTimeout) and AsyncAutomationClient#AsyncAutomationClient(String url, ExecutorService executor, long asyncAwaitTerminationTimeout) for the same reason.		5.7.1	Resolved	17/09/12
↓	NXP-10018	Improve XSD Types support in schema definition	Added support for more XSD types, see https://jira.nuxeo.com/browse/NXP-10053 for more upgrade notes		5.7.1	Resolved	04/09/12
↓	NXP-11045	NXP-11171 Make restDocumentLink create a link when there is no document	By default, the main tabs generate URLs with a document or a repositoryName. If you want to force your main tab to generate an URL only with a document, you need to specify it in its action properties. It's done for the Document Management tab: <action id="documents" link="view_documents" label="label.main.tab.documents" order="40"> <category>MAIN_TABS</category> <properties> <property name="requireDocument">true</property> </properties> </action>		5.7.1	Resolved	21/02/13