

Nuxeo Issue Tracker

JQL Query: project = "NXP" AND resolution = Fixed AND fixVersion = "9.2" AND ("Impact type" = "API change" OR "Upgrade notes" is not EMPTY) ORDER BY component ASC, key ASC

Sorted by: Component/s ascending, then Key ascending

1–26 of 26 as at: 03/08/17 10:56

Key	Summary	Impact type	Upgrade notes
NXP-21889	Unable to add ACL on a document with a computed group and virtual user	Configuration Change	You can use the property "nuxeo.automation.allowVirtualUser" to allow virtual user (non-existent user) usage in Nuxeo automation. If allowed, Nuxeo server will not check the user existence during automation execution. The default value is false. Set this property to true if you use Nuxeo computed user or computed group.
NXP-22190	Restore compatibility on automation		For backward compatibility with version prior to 9.1, you may want to inline the context in the scripting parameters by contributing the extension <pre><extension target="org.nuxeo.runtime.ConfigurationService" point="configuration"> <property name="nuxeo.automation.scripting.inline-context-in-params">true</property> </extension></pre>
NXP-22454	New dedicated method Blobs.createJSONBlob	API change	New class: JSONBlob New methods: Blobs.createJSONBlob Blobs.createJSONBlobFromValue Blobs.createJSONBlobFromValueJackson1
NXP-21877	CMIS query should take into account the maxItems parameter		We introduce a new <code>_query_</code> API, the <code>{{queryProjection}}</code> . This API allows you searching content the same you do with <code>{{queryAndFetch}}</code> , it also brings a way to paginate the results you'll get. As it, you can query your repository by paginating and projecting the result.
NXP-21456	Allow to relax document property check depending on configuration		With this feature, you're able to flag properties as deprecated or removed. Which is useful when you want to remove a property from your schema or rename/move it. Nuxeo Platform will also log messages for these properties in order to help developers to remove deprecated usage. Extension point documentation: XML extensions may contain any number of 'property' elements of the form: <pre><code> <property schema="common" name="size" deprecated="true" /> <property schema="file" name="filename" fallback="content/name" /> </code></pre> A property contributed to this extension point enables deprecation mechanisms inside Nuxeo Platform. This generates WARN message of usage to help to remove deprecated usage. <pre><p /></pre> A contribution is one of these types: <pre> deprecated: property still exists in schema definition, but it'll be removed in next version removed: property has been removed from schema definition, relax platform behavior. This will avoid Nuxeo property not found exceptions for remaining use of the property </pre> The fallback attribute is optional, its value has to be a xpath referencing an existing property in the same schema than removed/deprecated property. When presents, it is used: <pre> to set the value to the fallback property to get the value from the fallback property if it exists </pre> Note: for a deprecated property, <code>setValue</code> also set value to property and <code>getValue</code> get value from property if fallback value is null. <pre><p /></pre> For example, the contribution below enables WARN message of usage of property <code><i>file:filename</i></code> . This will also get/set the value from/to <code><i>file:content/name</i></code> for deprecated usage of <code><i>file:filename</i></code> property. <pre><code> <property schema="file" name="filename" fallback="content/name" /> </code></pre> As it, each usage of this property will automatically fallback on the fallback and avoid exception from platform. This will also allows to import document declaring the removed property.

Key	Summary	Impact type	Upgrade notes
NXP-22019	Improve internal change token for optimistic locking	API change	New behavior: - calling doc.putContextData(CoreSession.USER_CHANGE, Boolean.TRUE) then CoreSession.saveDocument(doc) will flag the save as a "user change".
NXP-22197	Paginate getChildren calls in BulkLifeCycleChangeListener		To enable pagination of getChildren in BulkLifeCycleChangeListener, you need to set to true the parameter nuxeo.bulkLifeCycleChangeListener.paginate-get-children in a contribution to ConfigurationService. You can also edit the page size depending on your needs (by default set to 500), by setting the parameter nuxeo.bulkLifeCycleChangeListener.get-children-page-size.
NXP-22217	Extract pure Blob APIs from the Blob APIs related to documents/repositories	API change	org.nuxeo.ecm.core.blob.BlobInfo is now used instead of the old org.nuxeo.ecm.core.blob.BlobManager.BlobInfo DocumentBlobProvider contains extracted APIs from BlobProvider dealing with documents: - freezeVersion(blob, doc) - getConvertedStream(blob, mimeType, doc) DocumentBlobManager contains extracted APIs from BlobManager dealing with documents: - readBlob(blobInfo, repositoryName) - writeBlob(blob, doc, xpath) - freezeVersion(doc) - getConvertedStream(blob, mimeType, doc) - notifyChanges(doc, xpaths) - garbageCollectBinaries - isBinariesGarbageCollectionInProgress - markReferencedBinary(key, repositoryName) The <blobdispatcher> configuration is now on the extension point <extension target="org.nuxeo.ecm.core.blob.DocumentBlobManager" point="configuration"> instead of the old <extension target="org.nuxeo.ecm.core.blob.BlobManager" point="configuration">
NXP-22259	Internal document version/timestamp (system change token)	Data Persistence Change	A new column "systemchangetoken" (for VCS) or a new field "ecm:systemChangeToken" (for DBS) is now written with each document and incremented automatically at each write.
NXP-21284	On a 100M documents repository, server can't start because of nuxeo-dam		Since 9.2, Picture facet is not dynamic anymore due to performance issue on big volume. If you want to make it dynamic again, you can override the facet definition and set perDocumentQuery to true, like this: <pre><facet name="Picture" perDocumentQuery="true"> <schema name="file"/> <schema name="picture"/> <schema name="image_metadata"/> </facet></pre> You'll need to require this component in your contribution "org.nuxeo.ecm.platform.picture.coreTypes".
NXP-21582	Move MongoDB Extension Directory to Nuxeo Platform		A new module has been added with the artifact coordinates "org.nuxeo.ecm.platform:nuxeo-platform-directory-mongodb"
NXP-22421	Database-level integrity constraints for PostgreSQL	Configuration Change	On VCS the repository configuration can now contain <childNameUniqueConstraintEnabled>true</childNameUniqueConstraintEnabled> This is available for PostgreSQL, and enabled by default.
NXP-21931	Make directory services more extensible		- A new module has been added with the artifact coordinates "org.nuxeo.ecm.platform:nuxeo-platform-directory-test" - The unit tests for directories (for SQL and MongoDB) are now located in this module. The backend to use to run these tests can be defined with the system property "nuxeo.test.directory". The available values are : * sql * mongodb If not set, the same backend as the repository will be used. If unknown by the directories, it will fallback on the sql configuration. - The 'DirectoryFeature' is now used for unit testing with directories. This feature will compute which template directory should be used according to the chosen backend.
NXP-22411	Generify directory references		A new descriptor for references in directories has been added. Example: <pre><references> <reference field="groups" directory="groupDirectory" name="user2group" source="userId" target="groupId" dataFile="user2group.csv"/> </references></pre>

Key	Summary	Impact type	Upgrade notes
			This reference is generic and can be used with SQL and MongoDB implementation.
NXP-19448	Migrate Nuxeo Target Platform as a Nuxeo Platform addon		The nuxeo-target-platforms-mp module has been removed as there is no need for a Nuxeo package of this addon
NXP-14830	Removing a user from a group (or deleting the group) for which the Read permission is granted on a folder synchronized for the given user is not detected as a deletion by Drive	API change	<p>Added:</p> <ul style="list-style-type: none"> - UserManager#getAncestorGroups(String groupId) - UserManager#notifyUserChanged(String userName, String eventId) - UserManager#notifyGroupChanged(String groupName, String eventId) - UserManager#notifyGroupChanged(String groupName, String eventId, List<String> ancestorGroupNames) <ul style="list-style-type: none"> - UserManagerImpl#USER_GROUP_CATEGORY - UserManagerImpl#ID_PROPERTY_KEY - UserManagerImpl#ANCESTOR_GROUPS_PROPERTY_KEY <ul style="list-style-type: none"> - NuxeoDriveGroupUpdateListener - NuxeoDriveEvents#GROUP_UPDATED
NXP-22320	Fix logging 'download' event continuously with Nuxeo Drive	API change	<p>Previously the 'webengine' reason was used for downloads coming from a WebEngine/Automation/REST API result.</p> <p>Now 'webengine' is used only for the subset of these that return a JSONBlob, otherwise the 'download' reason will be used.</p> <p>Downloads with 'webengine' reasons are not sent as download events by the DownloadService anymore (and therefore not logged in the audit).</p>
NXP-22550	Align requested fields on connect registration form when using nuxeoctl register-trial	API change	The synopsis has changed to "register-trial [<firstname> <lastname> <email> <company> <project>]"
NXP-22183	OAuth2: rework consumer registration	API change	<p>Added:</p> <ul style="list-style-type: none"> - OAuth2Client#redirectURIs - OAuth2Client#getRedirectURIs - OAuth2Client#OAuth2Client(String name, String id, String secret, List<String> redirectURIs) - OAuth2Client#isRedirectURIValid(String redirectURI) - OAuth2Client#toString() <p>Removed OAuth2Client(String name, String id, String secret)</p> <p>Added the redirectURIs field to the oauth2Client directory schema. When set through the JSF UI it is a required field and needs to be a comma-separated list of valid redirect URIs. A valid redirect URI must match this criterion: not be empty AND (start with https OR not start with http (e.g.: nuxeo://authorize) OR match the "http://localhost:(\d+)?(/.*)?" pattern (e.g.: http://localhost:8080/nuxeo))</p> <p>If the "redirect_uri" parameter is included when calling GET on /oauth2/authorize, it must match one of the redirect URIs defined in the oauth2Client:redirectURIs property of the registered OAuth2 client. Else the first redirect URI of the registered OAuth2 client is used.</p> <p>If the "redirect_uri" parameter was included when calling GET on /oauth2/authorize, it needs to be included when calling POST on /oauth2/token and both parameters must match.</p>
NXP-22523	Remove contributions registration on ClientRegistry service		<p>{{ClientRegistry}} class does not exist anymore but was replaced with {{OAuth2ClientService}}.</p> <p>If you were retrieving it, you should replace your code with:</p> <pre>{code} OAuth2ClientService clientService = Framework.getService(OAuth2ClientService.class); {code}</pre>
NXP-22617	Rename OAuth2 servlet path from /oauth2/authorization to /oauth2/authorize		The /oauth2/authorization endpoint has been renamed to /oauth2/authorize.
NXP-19326	Nuxeo Runtime Evolutions - Step 1		<p>If you upgrade, in order to make the hot reload work you need to add to your {{nuxeo.conf}} the following parameters :</p> <pre>{code} org.nuxeo.runtime.reload_strategy=unstash {code}</pre>

Key	Summary	Impact type	Upgrade notes
NXP-21969	graceful shutdown in tomcat	API change	On components, you could now provide a stopping logic by overriding the 'DefaultComponent#applicationStopped(ComponentContext, Instant)' method.
NXP-22131	Allow dynamic log4j.xml configuration changes	Configuration Change	<p>The configuration file lib/log4j.xml is now automatically scanned for changes dynamically while the server is running.</p> <p>This can be disabled by setting org.nuxeo.runtime.log4jwatch.disabled=true. The delay between two file checks can be changed from the default 10s using org.nuxeo.runtime.log4jwatch.delay=60.</p>
NXP-22212	Update and cleanup nuxeo-segment.io-connector		<ul style="list-style-type: none"> * Refactoring from Providers to Integrations : ** Extension point "providers" replaced by "integrations" ** Tags providersConfig/providers/provider replaced by integrationsConfig/integrations/integration ** Class SegmentIOProviders replaced by SegmentIOIntegrations * Class Group removed in favor of the one provided in analytics lib * No default cache config for the js script * No default openUrl config * Firstname and Lastname not sended by default on identify calls <p>These changes breaks the backward compatibility but we believe NOS team is the only one using this addon for now so we accept it</p>
NXP-22462	Fix segmentIO analytics version in dependencyManagement		com.github.segmentio:analytics managed version in nuxeo is now 1.0.7