

Nuxeo Issue Tracker

JQL Query: project = NXP AND status = Resolved AND fixVersion = "8.1" AND ("Impact type" is not EMPTY OR "Upgrade notes" is not EMPTY)

ORDER BY component DESC, key DESC

Sorted by: Component/s descending, then Key descending

1–8 of 8 as at: 29/01/16 12:34

Summary	Description	Votes	Created	Updated
Align smart search addon for 6.0 and LTS 2015	<p>Smart search addon has several issues before being released for 6.0:</p> <ul style="list-style-type: none"> some templates still need to be migrated to JSF2 related content view should be shown in the new "search tab" selected columns and sort management need to be aligned to the new search tab (smart search view was very close to the old advanced search view) save of smart query into a smart folder should be using the generic "save search" feature 	0	30/10/14	19/01/16
Use Environment.getDefault().getTemp() and nuxeo.tmp.dir	<p><code>Environment.getDefault().getTemp()</code> should be used instead of <code>System.getProperty("java.io.tmpdir")</code></p> <p>In the mean time, <code>nuxeo.tmp.dir</code> should be used instead of <code>java.io.tmpdir</code></p>	0	28/12/15	19/01/16
Unable to create new user with Multi Tenant addon	<p>Creating a new user and setting its password never create actually the user but only invite him.</p>	0	26/11/15	16/12/15
Rework liveconnect code	<p>Rework liveconnect code in order to have more common code among modules.</p>	0	23/12/15	15/01/16
Allow to use HTML content in tipsy tooltip	<p>Tipsy has a boolean parameter to allow to use html content inside tooltip.</p> <p>We should allow to use it.</p>	0	19/10/15	11/01/16
Add helpers to scaffold a JSF layout	<ul style="list-style-type: none"> The JSF tags available to reference a widget could be more explicit (instead of referencing <code>#{layout.widgetMap["widgetname"]}</code>) maybe reference all widgets in the context directly, by name (if adding more to the variables is not heavy on perfs) the widget id generation should be reviewed to allow referencing a widget directly, outside of the <code>nxl:layoutRowWidget</code> iteration tag maybe generate all local widgets, not only those referenced by rows add runtime tag libraries, allowing to reference a widget definition or widget type by tag name, instead of using <code>nxl:widget</code> and <code>nxl:widgetType</code> tags 	0	27/07/15	22/01/16
Fix S3 bucket property name	<p>The key used to specify a prefix in S3 conflicts with the bucket key in freemarker.</p> <p>In the S3 package, the bucket to use is specified by <code>nuxeo.s3storage.bucket</code>.</p> <p>Optionally, a prefix to use for the files in the bucket can be specified by <code>nuxeo.s3storage.bucket.prefix</code></p> <p>If the prefix is used, there is the following error on startup:</p> <pre>FreeMarker variables: ignored 'nuxeo.s3storage.bucket' conflicting with 'nuxeo.s3storage.bucket.[prefix]'</pre> <p>The <code>nuxeo.s3storage.bucket.prefix</code> will be replaced by <code>nuxeo.s3storage.bucket_prefix</code></p>	0	09/12/15	13/01/16
Allow separate repository DDL generation	<p>Nuxeo can now start with a new <code>nuxeo.vcs.ddlmode</code> parameter that specifies how the DDL for repository initialization should be executed at startup. Depending on the chosen mode, the DDL to be executed may not be executed at all and instead dumped to the file <code>log/ddl-vcs-default.sql</code>. The possible values for <code>nuxeo.vcs.ddlmode</code> are:</p> <ul style="list-style-type: none"> ignore: no DDL detected or executed; replaces <code>nuxeo.vcs.noddl=true</code> compat: compatibility mode with previous version, always executes DDL that recreates stored procedures (and does not attempt to detect existing ones); replaces <code>nuxeo.vcs.noddl=false</code> execute: executes the DDL and starts Nuxeo normally. dump: dump the DDL (if any) to the file but still executes it and starts Nuxeo normally. dump,ignore: dump the DDL (if any) to the file but does not execute it and starts Nuxeo normally (will likely result in errors). 	0	29/06/15	30/12/15

- **dump,abort:** dumps the DDL (if any) to the file, and if not empty aborts startup.

For Nuxeo 6.0 and Nuxeo 7.10 the default is

`nuxeo.vcs.ddlmode=compat`. For Nuxeo 8.1 the default will be `nuxeo.vcs.ddlmode=execute`.

Note that all this applies to the DDL for the document repository, but not DDL used by other users of SQL in the platform (directories, quartz, JPA persistence).
